

FORD ROAD 60'

5/8" IRON PIN FOUND

5/8" IRON PIN FOUND

S 78°46'00"E 657.84'
508.74'

PK NAIL SET

321.06'

S 80°41'00"E

227.18'

S 74°25'10"E 59.00'

WILLIAM & PENELOPE ROBINSON
VOLUME 830, PAGE 1290
1A-19-18

5/8" IRON PIN FOUND

5/8" IRON PIN FOUND

5/8" IRON PIN FOUND

5/8" IRON PIN FOUND

LOT 6, TRACT 5

LOT 8 TRACT 6

LOT 1 TRACT 6

N 0°35'13"W 1221.75'

DEED

FRANCES HADEN
DOC #200104166
1A-19-15

TIMOTHY HORTON & SHANNON KRIEGMONT
VOLUME 1009, PAGE 593
1A-19-2

14 6029 ACRES

HENRY ROGERS
VOL 891, PAGE 312
1A-19-3

CHESTER & RUTH LESLIE
VOL 826, PAGE 9
1A-19-17

DOROTHY BATES
VOL 326, PAGE 473

1A-17-1

IRON PIN SET

N 48°19'16"E 352.89'

5/8" IRON PIN FOUND

N 39°49'12"E 571.43'

5/8" IRON PIN FOUND

S 55°39'31"W 78.63'

5/8" IRON PIN FOUND

5/8" IRON PIN FOUND

S 21°05'06"W 180.73'



5/8" IRON PIN FOUND

MAP OF SURVEY FOR
TIMOTHY H HORTON & SHANNON W KRIEGMONT

KNOWN AS BEING PART OF LOTS 1 & 8,
TRACT 6 IN RANGE 6, TOWNSHIP 11 OF
THE CONNECTICUT WESTERN RESERVE
TOWNSHIP OF MADISON
COUNTY OF LAKE - STATE OF OHIO

THIS MAP OF SURVEY REPRESENTS A TRUE FIELD SURVEY PERFORMED BY ME ON FEBRUARY 7, 2003. DISTANCES ARE EXPRESSED IN FEET AND DECIMAL PARTS THEREOF IN ACCORDANCE WITH OHIO ADMINISTRATIVE CODE 4733-37. IRON PINS SET ARE 5/8" X 30" REBAR CAPPED "#7094". BEARINGS SHOWN HEREON ARE TO AN ASSUMED MERIDIAN AND ARE USED TO DENOTE ANGLES ONLY.

James A. Ziemba 2-7-2003
JAMES A. ZIEMBA, PROFESSIONAL SURVEYOR #7094



5/8" IRON PIN FOUND
S 24°36'18"W 15.70'

S 0°35'13"E 1367.32' OBS

1-1/2" IRON PIPE FOUND

LAKE COUNTY
GEAUGA COUNTY

BENCHMARK SURVEY COMPANY
5964 SOUTH RIDGE ROAD
MADISON, OHIO 44057-9741
FEBRUARY 7, 2003
1-440-428-8599