ARCOLE SHORE
ESTATES SUBDIVISION
VOLUME I, PAGE 71

SUBLOT 4

SUBLOT 5

0.19'

N 60°10'15"E
3.00'

5/8" CAPPED IRON PIN
FOUND (KEMPKE)

1" IRON
PIPE FOUND

IRON
PIN SET

N 60°10'15"E
103.11'

JAMES L. AHLIN
DOC. #2008R013547
1A-89C-8

SUBLOT 46

SUBLOT 47

N29°49'45"W 134.00'

ARCOLE ESTATES SUBDIVISION No. 2
VOLUME J, PAGE 87

SUBLOT 45

KIRK D. PEINE
DOC. #2002R019900
1A-89C-7

N 60°10'15"E
44.00'

S 29°49'45"E 300.00'

S 29°49'45"E
300.00'

JAMES AHLIN
1A-89C-8

N 29°49'45"W
166.00'

0.188 ACRES

0.710 ACRES

S 60°10'15"W
47.00'

IRON
PIN SET

S 60°10'15"W
103.11'

5/8" CAPPED IRON PIN
FOUND (KEMPKE)

5/8" CAPPED IRON PIN
FOUND (KEMPKE)

25.00'

307.36'

C1
90.38'

NORTON DRIVE 50'

ARCOLE DRIVE 50'

MAP OF SURVEY
FOR

KIRK D. PEINE

KNOWN AS BEING PART OF LOT 14
TRACT 1 IN RANGE 6, TOWNSHIP 12 OF
THE CONNECTICUT WESTERN RESERVE

TOWNSHIP OF MADISON

COUNTY OF LAKE - STATE OF OHIO

0' 15' 30' 60'
SCALE 1" = 30'

THIS MAP OF SURVEY REPRESENTS A TRUE FIELD SURVEY PERFORMED BY ME ON SEPTEMBER 5, 2008. IRON PINS SET ARE 5/8" X 30" REBAR CAPPED "BENCHMARK #7094". BEARINGS SHOWN HEREON ARE TO AN ASSUMED MERIDIAN AND ARE USED TO DENOTE ANGLES ONLY. DISTANCES ARE EXPRESSED IN FEET AND DECIMAL PARTS THEROF IN ACCORDANCE WITH OHIO ADMINISTRATIVE CODE 4733-37.

9-9-2008
JAMES A. ZIEMBA PROFESSIONAL SURVEYOR #7094

STATE OF OHIO
JAMES A.
ZIEMBA
7094
REGISTERED
PROFESSIONAL SURVEYOR

Curve	Delta Angle	Radius	Arc	Tangent	Chord	Chord Bearing
1	9°30'15"	544.87	90.38	45.30	90.28	S 64°55'22"W

BENCHMARK SURVEY COMPANY
5964 SOUTH RIDGE ROAD
MADISON, OHIO 44057
1-440-428-8599
SEPTEMBER 5, 2008